

Features:

- Hi fidelity 4" surface mount speaker system
- Suitable for indoor or outdoor use
- Smooth-wide frequency response
- Excellent fidelity for music or voice
- 4 inch polypropylene woofer cone
- Rubber woofer surround
- 12 oz ported ferrite woofer magnet
- 1 inch silk dome tweeter
- Neodymium tweeter magnet
- PTZ tweeter protection with auto reset
- High quality crossover with air core inductors
- Aluminum non-rusting grille
- Multi-position pivoting mounting bracket included
- Gold plated 14awg binding posts
- Includes seismic anchor and safety cable
- Includes internal 15watt 25/70 volt transformer
- Sold as pairs
- Master carton 2 pairs
- 1 year warranty



Specifications:

- Diameter Woofer 4" (101.6mm) polypropylene
- Diameter Tweeter 1" (25.4mm) silk dome
- Power Handling 100 watts (peak) 50 watts RMS
- Impedance 8 ohms (nominal)
- Frequency Response 100Hz - 22kHz (± 10 dB)
- Dispersion 95 °
- Sensitivity 94dB (1W 1M) Average
- Grille material Aluminum
- Color White

Included:

- Internal transformer 15 watts 25/70 volt
- Wattage taps 15w, 7.5w, 4w, 2w & 8ohms
- Pivoting powder coated steel mounting brackets x 2
- Seismic anchors x 2
- Aircraft quality safety cable x 2

Dimensions:

- Dimensions Overall
- Height 9.5" (241.3mm)
- Width 6.25" (158.75mm)
- Depth 7" (177.8mm) including bracket
- Shipping Weight 10.25lbs (4.65kg) per pair

