

### Features :

- Two-way passive high SPL Coaxial loudspeaker
- Perfect for bars, restaurants, gyms .etc where higher SPL is required
- Solid 20mm Birch Multi-ply cabinet construction
- Ultra compact design only W 11" x H 10" x D 14"
- Steel powder coated grill (dent resistant)
- High power 10" coaxial woofer
- High power phase corrected compression horn
- Titanium diaphragm
- Horizontal or vertical mounting
- Audiophile grade internal crossover
- High frequency protection circuit
- Includes heavy duty steel mounting bracket
- Tough-coat painted textured finish
- Can be used indoors or outdoors (under cover)
- Locking Speakon in/out



### Specifications:

- 75Hz- 20kHz
- Sensitivity 100dB 1W/1M
- Impedance 8 ohms (nominal)
- Crossover 2.5kHz
- Dispersion 60 x 60 degrees
- Max SPL 123 dB

### LF:

- 10" steel frame basket
- Treated pulp fiber cone
- 3" edge wound copper/aluminum voice coil
- 50oz Ferrite magnet structure
- 200 watts RMS 400 watts program

### HF:

- 1" throat diameter
- 1.75" voice coil
- 30oz Ferrite magnet structure
- 40 watts RMS
- Dual Speakon connections
- Powder coated steel fully adjustable U bracket

### Dimensions:

- (W) x11.6"/297mm
- (H) x 10.6"/270mm
- (D) x 10.5"/266mm
- (D)x 13.5"/342mm W/ bracket
- Weight: 17.5Kg/38.5 lbs

Requires SPK-4P Connectors



Horizontal or vertical mounting



Heavy Duty 200WRMS/400W Program Coaxial Driver

