

Features:

- High power handling 6.5" stereo speaker system
- New trim-less magnetic grille
- Smooth-wide frequency response
- 6.5 inch woven Kevlar woofer cone
- Dual voice coils accepts left & right signals
- Rubber woofer surround
- 20 oz Ferrite woofer magnet
- Dual 1 inch aim-able silk dome tweeters
- Neodymium tweeter magnets
- 15 degree opposing tweeter angles
- Minimal tweeter cancellation
- Dual crossovers with air core inductors
- PTZ tweeter protection with automatic reset
- 4 heavy duty "Tough-Cam" mounting clamps.
- Gold plated 12awg binding posts
- Complete rough in bracket included (RI-675)
- Paint able to match any decor
- Sold as each
- Master carton 2pcs
- 10 year warranty



Specifications:

- Diameter Woofer 6.5" (165.1mm) woven Kevlar
- Voice coils - Dual edge wound copper
- Diameter Tweeters 1" (25.4mm) silk dome aim-able
- Power Handling 120 watts (peak)
- Impedance 8 ohms left/right (nominal)
- Frequency Response 40Hz - 22kHz (± 10 dB)
- Dispersion 110°
- Sensitivity 92dB (1W 1M) Average

Included:

- RI-675 rough-in bracket
- Cutout template
- Paint shield

Dimensions:

- Dimensions Overall 10.125" (250mm)
- Cutout Dimensions Speaker 8.25" (210mm)
- Cutout Dimensions RI Bracket 8.5" (216mm)
- Depth 3.5" (90mm)
- Shipping Weight 14lbs (6.3kg) master carton 2pcs
- Shipping dimensions 14x12x13" master carton 2pcs

