

Features :

- Two single diversity UHF wireless-microphone systems
- 165 Select-able UHF channels-per microphone
- Auto scan function (finds open frequencies automatically)
- Wide frequency hand-held microphones
- Mic's operate on two AA batteries
- Infrared microphone auto sync function
- Excellent feedback rejection
- Cardioid pickup pattern
- Integrated ON/OFF switch
- Dual 3 Pin balanced XLR outputs & 1/4" unbalanced mixed output
- Receiver with LCD display
- Includes:
 - 3' XLR cable
 - 2 x AA batteries
 - Power supply
 - Rack kit



Specifications Each Receiver:

- Carrier wave freq range - UHF 516-541MHz
- Oscillation Mode – Phase-lock loop controlled
- Carrier wave stability - 10PPM
- Sensitivity – 100dB @ sinad= 12dB
- S/N ratio – 80dB
- THD - <0.8% @ 1kHz
- Image rejection – 85dB
- Spurious rejection – 75dB
- Frequency response – 50Hz-16kHz
- AF Output impedance – 2.2k ohms
- Max output level – 0-400mv bal / 0-200mv unbal
- Display type – LCD
- Power supply – 600mA 14 VDC Included

Hand-held Transmitters:

- Capsule Type – Moving coil dynamic
- Pickup pattern- Cardioid
- Frequency Response – 50Hz- 16kHz
- Sensitivity - (-74dB +/- 3dB)
- ON/OFF switch – Yes
- Power – 30mW
- Spurious Emission<40dB (with carrier)
- Display – LED
- Battery voltage 1.5V x 2 AA batteries
- Battery life- 8 hours approx

Dimensions: (W x D x H)

- W= 6.75"/175mm x
- D= 5"/130mm
- H=1.75"/44mm
- Shipping Weight 5.5 lbs (2.5kg)

Includes Rack Mounting Kit

