



Rigid Casters (Zinc Plated)

4" 5" 6" and 8" Diameter, 2" Wide

Caster Specifications

314 Axminister Dr.
Fenton, MO 63026

(866) 206-8792



Fastening Options Available

Type	Size	Fastening Code	Available on Caster Diameter:
Top Plate	Overall 4" x 4-1/2", Holes 2-3/8" x 3-5/8" TO 3" x 3"	44	4" 5" 6" 8"
Top Plate	Overall 4-1/2" x 6-1/4", Holes 2-7/16" x 4-15/16" TO 3-3/8" x 5-1/4"	46	4" 5" 6" 8"
Top Plate	Overall 5" x 5-1/2", Holes 4-1/8" x 4-1/2"	55	6" 8"

Top Lock Brake Option



Code "T"

When ordering a brake option, change the first "X" at the end of the model number to "T". For example change "...XX" to "...TX".

Wheel Dia.	Tread Width	Wheel Type	Bearing Type	Tread Color	Tread Type	Durometer (Hardness) (* +/- 5)	Temp. Range Fahrenheit	Mounting Height	Swivel Radius	Load Cap. lbs.	Model Number *	Fastening Codes Available
4"	2"	Polyolefin (Plastic)	Roller	Black	Flat	70 Shore D	-20 to +180	5-1/2"	3-1/4"	500	Z20R40PO04BF__XX	44, 46
		Phenolic		Black	Flat	90 Shore D	-50 to +250			800	Z20R40PH04BF__XX	
		Polyurethane on Iron		Green	Flat	95 Shore A	-40 to +180			800	Z20R40PI04GF__XX	
		Polyurethane on Polyolefin		Maroon	Flat	90 Shore A	-20 to +180			700	Z20R40PP04MF__XX	
		Solid Polyurethane		Blue	Flat	60 Shore D	-50 to +180			750	Z20R40SU04LF__XX	
		Semi-Steel		Silver	Flat	Brinell 145	-45 to +600			700	Z20R40SS04SF__XX	
		Thermoplastic Rubber (TPR)		Grey	Flat	75 Shore A	-20 to +180			300	Z20R40TP04AF__XX	
		Thermoplastic Rubber (TPR)		Grey	Round	75 Shore A	-20 to +180			300	Z20R40TP04AR__XX	
5"	2"	Polyolefin (Plastic)	Roller	Black	Flat	70 Shore D	-20 to +180	6-1/2"	4"	650	Z20R50PO04BF__XX	44, 46
		Polyolefin (Plastic)		White	Flat	70 Shore D	-20 to +180			650	Z20R50PO04WF__XX	
		Phenolic		Black	Flat	90 Shore D	-50 to +250			1,000	Z20R50PH04BF__XX	
		Polyurethane on Iron		Green	Flat	95 Shore A	-40 to +180			1,100	Z20R50PI04GF__XX	
		Polyurethane on Polyolefin		Maroon	Flat	90 Shore A	-20 to +180			750	Z20R50PP04MF__XX	
		Solid Polyurethane		Blue	Flat	60 Shore D	-50 to +180			900	Z20R50SU04LF__XX	
		Semi-Steel		Silver	Flat	Brinell 145	-45 to +600			1,000	Z20R50SS04SF__XX	
		Thermoplastic Rubber (TPR)		Grey	Flat	75 Shore A	-20 to +180			350	Z20R50TP04AF__XX	
		Thermoplastic Rubber (TPR)		Grey	Round	75 Shore A	-20 to +180			350	Z20R50TP04AR__XX	
		6"		2"	Polyolefin (Plastic)	Roller	Black			Flat	70 Shore D	
Polyolefin (Plastic)	White		Flat		70 Shore D		-20 to +180	700	Z20R60PO04WF__XX			
Phenolic	Black		Flat		90 Shore D		-50 to +250	1,200	Z20R60PH04BF__XX			
Polyurethane on Iron	Green		Flat		95 Shore A		-40 to +180	1,200	Z20R60PI04GF__XX			
Polyurethane on Polyolefin	Maroon		Flat		90 Shore A		-20 to +180	900	Z20R60PP04MF__XX			
Solid Polyurethane	Blue		Flat		60 Shore D		-50 to +180	1,000	Z20R60SU04LF__XX			
Semi-Steel	Silver		Flat		Brinell 145		-45 to +600	1,200	Z20R60SS04SF__XX			
Thermoplastic Rubber (TPR)	Grey		Flat		75 Shore A		-20 to +180	500	Z20R60TP04AF__XX			
Thermoplastic Rubber (TPR)	Grey		Round		75 Shore A		-20 to +180	500	Z20R60TP04AR__XX			
8"	2"		Polyolefin (Plastic)		Roller		Black	Flat	70 Shore D	-20 to +180	8-1/2"	6"
		Polyolefin (Plastic)	White	Flat		70 Shore D	-20 to +180	900	Z20R80PO04WF__XX			
		Phenolic	Black	Flat		90 Shore D	-50 to +250	1,250	Z20R80PH04BF__XX			
		Polyurethane on Iron	Green	Flat		95 Shore A	-40 to +180	1,250	Z20R80PI04GF__XX			
		Polyurethane on Polyolefin	Maroon	Flat		90 Shore A	-20 to +180	1,000	Z20R80PP04MF__XX			
		Solid Polyurethane	Blue	Flat		60 Shore D	-50 to +180	1,000	Z20R80SU04LF__XX			
		Semi-Steel	Silver	Flat		Brinell 145	-45 to +600	1,250	Z20R80SS04SF__XX			
		Thermoplastic Rubber (TPR)	Grey	Flat		75 Shore A	-20 to +180	600	Z20R80TP04AF__XX			
		Thermoplastic Rubber (TPR)	Grey	Round		75 Shore A	-20 to +180	600	Z20R80TP04AR__XX			

* Complete the model number by filling in the blank with a Fastening Code from the table above.